

**Product Code: TXSK**

**FEATURES/APPLICATIONS :**

- Premium warp-knitted polyester fabric
- Super soft and lightweight
- 2-direction good stretch makes it ideal for hanging banner, tradeshow, Pop-up, etc.
- Great definition for excellent quality printing
- Coated for dye-sub direct printing and also suitable for dye-sub transfer

**PRINTER COMPATIBILITY:**

D-Gen Teleios, Dupont Artistri, Durst Rhotex 320, Jeti 3324 AquaJet, Mimaki JV5-320DS Mimaki DS-1600, Mimaki DS-1800, Mutoh Viper TX, Roland HeatWave DFP-74 and Roland Hi-Fi Express printers, Reggiani ReNOIR

**MATERIAL DETAILS:**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	180g/sq.m	5.2 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	83x110 dtex	75x100 denier
Weave Method	N/A	Warp-knitted 2 bar	
White Point	CIE/D65	≥125	
Shrinkage	N/A	≤2% ( 190°C , 1min )	
Elasticity	Length*Width=200*50mm , Speed=100mm/min ,	Warp : 19.5% Weft : 9.5%	
Flame Resistance	/	NFPA 701, DIN 4102-1-B1	
Recommend fixation	N/A	190°C-210°C , 1-2min	
Transfer temperature	N/A	190°C-210°C , 1-2min	
Yellowing temperature	SUPRKC REX-C400	240°C	
Width	N/A	Max 320cm	126"
Standard Length	N/A	50m	55yd

**INK PRINTABILITY**

Solvent	Eco Solvent	UV	Latex
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>	<input type="checkbox"/>	

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.