

**Product Code:** TXIlluminate

**Features:**

- 100% polyester that has been bath coated and then coated again on one side with resin, which allows you to print solvent and UV.
- More white & quality, very tight structure makes it ideal for backlit or front lit graphics as well as indoor and short-term outdoor
- Produces flawless high quality images when rear-illuminated.

**Applications:**

- Led light boxes
- Frame systems
- Pop-up tents
- Sun-umbrellas

**Material Details:**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	180g/sq.m	5.2 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Weave Method	N/A	Woven	
White Point (CIE/D65)	CIE86/ASTME313-00(D65/10,SCI)	≥109	
Shrinkage	N/A	≤2% (190°C, 1min)	
Flame Resistance	/	DIN 4102-1-B1,NFPA 701	
Recommend fixation temperature	N/A	190°C-210°C, 1-2min	
Transfer temperature	N/A	190°C-210°C, 1-2min	
Yellowing temperature	SUPRKC REX-C400	170°C (sticky)	
Width	ASTM D751-2006	Max 320cm	126"
Standard Length	ASTM D751-2006	50m	55yd

**INK PRINTABILITY**

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>		

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.