

Product Code: TX3W

Features:

- Heavy woven fabric gives it good opacity
- White structure, fabulous in appearance

Applications:

- Soft Signs Backlit Systems
- Display Systems

Material Details:

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	250g/sq.m	7.5 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	83x330 dtex	75x300 denier
Weave Method	N/A	Woven	
White Point (CIE/D65)	CIE86/ASTME313-00(D65/10,SCI)	≥116	
Shrinkage	N/A	≤2% (190°C , 1min)	
Flame Resistance	/	DIN 4102-1-B1,NFPA 701	
Recommend fixation temperature	N/A	190°C-210°C , 1-2min	
Transfer temperature	N/A	190°C-210°C , 1-2min	
Yellowing temperature	SUPRKC REX-C400	250°C	
Width	N/A	Max 320cm	126"
Standard Length	N/A	50m	55yd

Ink Printability:

Solvent	Eco Solvent	UV	Latex
			<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	
	<input type="checkbox"/>	<input type="checkbox"/>	

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.