

Perfect Fit SEG Display

Product Code: TXPFSEG

Material: 100% polyester

Weight: 220gsm

Product Specifications:

Specifications	Metric	Imperial	Test Method
Material	100% polyester	100% polyester	DIN 60001, ASTM D7641
Weight	220 g/sq.m	6.4 oz/sq.yd	DIN EN ISO 2286-2, ASTM D751
Shrinkage	<=2%		190°C, 1 min
Shielding Rate	(50+/-4)%		ANSI PH2. 19, ISO 5/2
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, NF P92 M1		DIN 4102-1-B1, NFPA 701 Test 1, NF P92 M1
Recommended Fixation Temp.	190°C-210°C, 1-2 min		
Transfer Temp.	190°C-210°C, 1-2 min		
Yellowing Temp.	<= 210°C		SUPRKC REX-C400, 30s
Maximum Width	320 cm	126"	DIN EN ISO 3759, ASTM D751-2006
Standard Length	50 m	55 yards	DIN EN ISO 3759, ASTM D751-2006

Applications:

- Display
- Pop Up
- Backdrops

Compatible Inks:

- Dye-Sub Transfer
- Dye-Sub Direct
- Latex