

Product Code: Textent

Description: 100% Polyester woven tent fabric

Features:

- 100% Polyester woven, one side acrylic coating, water resistant, matte.
- 600D x 600D woven base fabric with super strong tensile and tear strength.
- Combined with UV resistant, solvent and latex or dye-sublimation inks

Applications:

- Tent
- Tradeshow
- Events
- Outdoor

Material Details:

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	270g/sq.m	7.9 oz/sq.yd.
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	660x660 dtex	600x600 denier
Weave Method	N/A	Woven	
Shrinkage	N/A	≤3% (190°C, 1min)	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend fixation temperature	N/A	190°C-210°C, 1-2min	
Transfer temperature	N/A	190°C-210°C, 1-2min	
Yellowing temperature	SUPRKC REX-C400, 30s	≥210°C	
Width	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yd

Ink Printability:

- Solvent
- Eco-Solvent
- UV
- Dye Transfer
- Dye Direct